



## STANDARD FEATURES



|                                |                            |
|--------------------------------|----------------------------|
| Control panel                  | <b>ELECTRONIC DIGIT3</b>   |
| Wash arm                       | <b>1 - Stainless steel</b> |
| Rinse arm                      | <b>2 - Stainless steel</b> |
| Detergent injector             | <b>Optional</b>            |
| Rinse aid injector             | <b>-</b>                   |
| Peristaltic rinse aid injector | <b>Standard</b>            |
| Break tank                     | <b>Optional</b>            |
| Water softener                 | <b>Optional</b>            |
| Drain pump                     | <b>Optional</b>            |
| Diagnose Wi-Fi                 | <b>-</b>                   |

## TECHNICAL FEATURES

|                             |                             |              |           |
|-----------------------------|-----------------------------|--------------|-----------|
| External size               | <b>473x513x689</b>          | <b>LxPxH</b> | [mm]      |
| Overall size                | <b>855</b>                  | <b>DOA</b>   | [mm]      |
| Clearance                   | <b>315</b>                  | <b>A</b>     | [mm]      |
| Maximum height for crockery | <b>300</b>                  | <b>Au</b>    | [mm]      |
| Rack size                   | <b>400x400</b>              |              | [mm]      |
| Tank size                   | <b>14</b>                   |              | [lt]      |
| Rinse water consumption     | <b>2,4</b>                  |              | [lt]      |
| Wash pump                   | <b>0,17</b>                 |              | [kW]      |
| Tank heater element         | <b>1,6</b>                  |              | [kW]      |
| Booster heater element      | <b>2,8</b>                  |              | [kW]      |
| Installed load              | <b>3,0</b>                  |              | [kW]      |
| Cycles                      | <b>60 / 120 / 180 / 480</b> |              | [sec]     |
| Output cycles per hour      | <b>60 / 30 / 20 / 8</b>     |              | [cycle/h] |
| Electrical supply           | <b>230V/50Hz</b>            |              |           |
| Noise                       | <b>48</b>                   |              | [dBA]     |
| Weight                      | <b>34</b>                   |              | [kg]      |

Theoretical data with water supply at 55°C  
 Where water hardness exceeds 8,43°e, a water softener is required. Not suitable for hot water over 30°C  
 Dimension depending on the type of basket used.



## STANDARD EQUIPMENT

Hoses (1 for each): Water connection, drain, transparent for rinse product  
2 universal baskets, 1 cutlery rack

## GENERAL FEATURES

- Double-skinned cabinet and door.
- Tank and door made of stainless steel AISI 304.
- Easy-clean-dual-filter system.
- Pressed basket guides in the tank.
- Monobloc wash pump fixed directly to the tank.
- A stainless-steel wash arm and two rinse arms of composite material, independent and rotary.
- Peristaltic rinse aid auto-dosing unit, adjustable from control panel.
- Stand-by system for energy saving
- Electronic control panel with high-resolution colour TFT 45x60mm screen for easy use of the machine.
- Four purpose-designed washing cycles for various types of crockery to be washed.
- Two menu levels: an operator and a technical menu, protected by a pin code (after-sales service).
- Counter of daily and total number of cycles.

## PERFORMANCES

|   | 55°C<br>nom. | 15   | 20   | 25   | 30   | 35   | 40   | 45   | 50   | 55   | 60   | [°C]     |
|---|--------------|------|------|------|------|------|------|------|------|------|------|----------|
| Supply water temperature  |              |      |      |      |      |      |      |      |      |      |      |          |
| Maximum cycles feasible in continuous operation                 | <b>48</b>    | 23   | 25   | 27   | 29   | 32   | 36   | 41   | 48   | 48   | 48   | [rack/h] |
| Total spending power from single-skin machine                   | -            | -    | -    | -    | -    | -    | -    | -    | -    | -    | -    | [kW]     |
| Total spending power from double-skin machine                   | <b>3,01</b>  | 2,95 | 2,95 | 2,95 | 2,94 | 2,94 | 3,03 | 3,02 | 3,01 | 3,01 | 3,01 | [kW]     |
| Sensible heat emitted into the room from single-skinned machine | -            | -    | -    | -    | -    | -    | -    | -    | -    | -    | -    | [kW]     |
| Sensible heat emitted into the room from double-skinned machine | <b>0,33</b>  | 0,36 | 0,36 | 0,36 | 0,35 | 0,35 | 0,34 | 0,34 | 0,33 | 0,33 | 0,33 | [kW]     |
| Latent heat emitted into the room                               | <b>0,61</b>  | 0,14 | 0,17 | 0,20 | 0,24 | 0,29 | 0,36 | 0,44 | 0,56 | 0,61 | 0,67 | [kW]     |
| Emitted standby power with closed door in single-skin machine   | -            | -    | -    | -    | -    | -    | -    | -    | -    | -    | -    | [kW]     |
| Emitted standby power with closed door in double-skin machine   | <b>0,12</b>  | 0,12 | 0,12 | 0,12 | 0,12 | 0,12 | 0,12 | 0,12 | 0,12 | 0,12 | 0,12 | [kW]     |