



SHD 50 - 40 LCD

Hood

FEATURES

Control Panel
Cabinet
Washing Arm
Rinse Arm
Full AISI 304 stainless steel wash tank for maximum hygiene and durability
Rinse aid Dosing
Break Tank and rinse booster pump
Drain Pump
Detergent Dosing
Water Softener
CRV - Heat Recovery and Steam Condenser 0,12kW
Boosted Boiler 9 kW
Integrated osmosis unit
Automatic Hood
Switch

Standard

LCD
Double Skin
4 - Superwash
4 - Stainless Steel
•
Peristaltic
•

Optional

•
•
•
•
•
•
•

TECHNICAL FEATURES

External Dimensions	1181x796x1500	WxDxH mm
Overall Open Door	1950	mm
Maximum Washing Height	400	mm
Clearance	430	mm
Basket Dimensions	500x500	mm
Tank Dimension	60	lt
Water Consumption	4,7	lt/Cycle
Wash Pump	N°2 x 0,52	kW
Tank Heater Element	7,5	kW
Boiler Heater Element	12	kW
Installed Power	13,04	kW
Washing Cycles	60/120/180/480	Sec
Output Cycles for Hour	60/30/20/8	Cycles/H
Power Supply	400V/3N/50Hz	
Noise	69	dBA
Weight	200	Kg
Inlet water	55/7-12	C/°f
	1,5/3	bar

ACCESSORIES

Hoses (1 per each): Water Loading/Draining, Transparent for rinse aid with dipstick
 Baskets: 4x18 Plates, 2 Universal Basket, 4 Cutlery Basket

TECHNICAL DRAWINGS

