



SD 50 - 37 LCD

Undercounter

## FEATURES

- Control Panel
- Cabinet
- Washing Arm
- Rinse Arm
- Full AISI 304 stainless steel wash tank for maximum hygiene and durability
- Rinse aid Dosing
- Drain Pump
- Detergent Dosing
- Water Softener
- Break tank and rinse booster pump
- Switch
- Integrated osmosis unit

## Standard

- LCD
- Double Skin
- 2 - Stainless Steel
- 2 - Stainless Steel
- 
- Peristaltic

## Optional

- 
- 
- 
- 
- 
- 

## TECHNICAL FEATURES

External Dimensions	604x633x838	WxDxH mm
Overall Open Door	1072	mm
Maximum Washing Height	370	mm
Clearance	400	mm
Basket Dimensions	500x500	mm
Tank Dimension	11	lt
Water Consumption	2,3	lt/Cycle
Wash Pump	0,55	kW
Tank Heater Element	2	kW
Boiler Heater Element	6	kW
Installed Power	6,55	kW
Washing Cycles	60/120/180/480	Sec
Output Cycles for Hour	60/30/20/8	Cycles/H
Power Supply	400V/3N/50Hz	
Noise	68	dBA
Weight	58	Kg
Inlet water	55/7-12 1,5/3	C/°f bar

## ACCESSORIES

- Hoses (1 per each): Water Loading/Draining, Transparent for rinse aid with dipstick, Red Hose for Detergent
- Baskets: 2x18 Plates, 1 Universal Basket, 1 Cutlery Basket



**SILANOS**  
Clean efficiency

EN

## TECHNICAL DRAWINGS

The data, information, and images contained in this document are for informational purposes only and do not constitute a contractual obligation. The company reserves the right to update them without prior notice.

